

# Data Protection Solution

## NEC T09A2 TAPE LIBRARY

**AUTOMATED BACKUP SOLUTION WITH HIGH STORAGE CAPACITY IN A REDUCED SPACE**



### PERFORMANCE

### SIMPLIFIED OPERATION

### COMPACT

#### 1U Rack space

The NEC T09A2 tape library offers a cost-effective and space efficient data protection solution for SMB and organizations with limited rack space to automate their backup processes to reduce the need for manual intervention and the risk of human error.

#### Advanced bar-code reader

The NEC T09A2 tape library uses an advanced bar code reader to register the location of LTO bands. She is equipped with one removable magazine, and is capable of storing up to 14.4TB of data in only 1U of rack space.

#### Intuitive Administration

It includes a remote management system to facilitate off-site data management and to offer a reliable protection. The management can be made either on the LCD screen situated in library front, or remote, via a intuitive Web interface, since any browser.

#### Compatibility

Compatible avec les principaux logiciels de sauvegarde comme Symantec Backup Exec et BrightStor ARCserve.

**HARDWARE SPECIFICATION**

**Performances**

- Supports LTO-4 tape via SAS connexion.
- Delivers up to 120MB/sec native transfers rates.

**Compact design**

- 1U compact rack solution with 9 cartridges for a native capacity of up to 7.2TB.

**Simplified operation**

- Thanks to one removable magazine design that allows to manage 9 cartridges including 1 useful as mail box. The tape drive can be imported and exported individually via the mail box.

**Open solution**

- Supports most of the operating systems such as Microsoft Windows and Linux.

Drive type	LTO Ultrium 4	
Number of drives	1	
Number of cartridges	9	
Maximum data capacity *1	7.2TB (native) 14.4TB (compressed at 2:1)	
Transfer rate *2	120MB/sec (native) 240MB/sec (compressed at 2:1)	
Mail box (dedicated slots for importing/exporting cartridges)	1 slot	
Barcode reader	Standard	
Host interface	SAS	
Performance	Cartridge access time	30 sec (average)
	Initialize time	Less than 150 sec
Robotics reliability	MSBF	More than 1,000,000 swaps
	MTBF	250,000 hours (power-on hours)
Power requirement	AC100-240V, 50/60Hz (auto-ranging)	
Power consumption	110W (maximum)	
Environmental limits	Temperature	10°C to 35°C (50°F to 95°F)
	Humidity	20% to 80%H (non-condensing)
Dimensions (h x w x d)	44 x 483 x 850 (mm)	
Weight	Less than 13kg (28.7lbs.)	
Os support	Windows® Server et Storage, HP-UX, Solaris™, AIX®, Linux®	
Backup software support	VERITAS Backup Exec, CA ARCserve, Tivoli, BakBone NetVault, Legato NetWorker, DataProtector	
Warranty	3 years on site D+1 in standard	

Pack content (1x library, rails kit, SAS 3mn Data Cable, 1x LTO cleaning cartridge)

\*1 1GB = 1,000,000,000 bytes

\*2 Data transfer rate would differ due to operating environment and conditions.

\* Need SAS3442E-R Host Bus Adapter to connect library on server

@2010 NEC. The information and specification contained in this publication are subject to modification without prior notice. All other names of products and brands cited are the property of their respective owners. Products can be photographed with the optional components available. NEC declines all responsibility in the case of photographic or typing errors. Photos and documents are not contractual.

Ref : Datasheet- uk / NEC T09A2 TYPE LIBRAIRY January 2010

**NEC European Headquarters**  
 Immeuble optima - 10, rue Godefroy  
 92821 Puteaux Cedex - France  
[www.nec.com](http://www.nec.com)

Tel: +33 1 42 91 80 00  
 Fax: +33 1 42 91 88 61

Empowered by Innovation **NEC**